

Basic Technical Data

nominal electrical output	2000	kW
maximum heat output ¹⁾	2138	kW

load	50	75	100	%
maximum heat output	1237	1688	2138	kW
fuel input	2535	3588	4651	kW
electrical efficiency	39,4	41,8	43,0	%
heat efficiency	48,8	47,0	46,0	%
total efficiency (fuel utilization)	88,2	88,8	89,0	%
gas consumption	390	552	716	Nm ³ /hr

The Basic Technical Data are applicable for the standard conditions pursuant to the "Technical instructions" document.

The minimum permanent electrical output must not drop below 50 % of the nominal output.

Gas consumption is mentioned for biogas with methane content 65%, at normal conditions (0°C, 101,325 kPa).

Gas consumption tolerance, or fuel input tolerance, at 100% load is +5%.

Tolerance of other parameters are mentioned in "Technical Instructions-Validity of Technical Data" document.

1) Maximum heat output is a sum of heat outputs of secondary circuit with exhaust gas cooled to 150°C and aftercooler circuit

Observance of Emission Limits

emissions	NOx	CO	
with 5% of O ₂ in exhaust gases	500	650	mg/Nm ³

Generator

type	MJB 560 LA4
producer	MARELLI
cos φ	0,8/1,0
efficiency in the working point	97,3 %
voltage	400 V
frequency	50 Hz

Engine

type	TCG 2020 V20
producer	MWM
number of cylinders	20
arrangement of cylinders	V
bore × stroke	170/195 mm
displacement	89 dm ³
compression ratio	14 : 1
speed	1500 rpm
nominal oil consumption	0,15 g/kWh
max. engine output	2055 kW

TCG 2020V20 BG65% CH₄ ; 30.1.2017

Thermal System

Secondary Circuit

heat carrier	water
circuit's heat output	2015 kW
nominal water temperature, input / output	70/90 °C
nominal temperature drop	20 °C
return water temperature, min / max	40/70 °C
nominal flow rate	24,1 kg/s
max. working pressure	600 kPa
min. pressure in system	100 kPa
water volume in CHP unit circuit ¹⁾	2000 dm ³
pressure loss at the nominal flow rate ¹⁾	90 kPa

1) total value (engine-generator in sound enclosure and exhaust gas module without connecting pipeline)

Utilization of exhaust gas output for other purposes

heat output of exhaust gases (cooling to 150°C)	936 kW
exhaust gas temperature	434 °C

Primary Circuit

heat carrier	water + ethylene glycol
ethylene glycol's concentration	35 %
circuit's heat output	1079 kW
max. working pressure	300 kPa
water volume in CHP unit circuit	420 dm ³



Aftercooler Circuit

heat carrier	water + ethylene glycol	
ethylene glycol's concentration	35	%
circuit's heat output	123	kW
coolant temperature (outlet from CHP unit – informative)	53,0	°C
coolant temperature (inlet into CHP unit) max	50,0	°C
nominal flow rate	11,1	kg/s
pressure reserve at the nominal flow rate ¹⁾	70	kPa
highest allowed maximal hydrostatic height of system	10	m
maximal connect-able volume of system outside the module of CHP unit ³⁾	250	dm ³
max. working pressure	300	kPa
min. working pressure	50	kPa
water volume in CHP unit circuit	80	dm ³

1) pressure reserve of internal part for covering pressure losses of external parts of circuit (interconnection pipeline and dry cooler)

2) if connected volume overstep mentioned value, it is necessary to install into system additional expansion vessel

Fuel, Gas Inlet

methane content	65	%
minimal methane content	> 45	%
low heat value	23,4	MJ/Nm ³
gas pressure	6	kPa
max. pressure change under varying consumption	10	%
max. gas temperature	35	°C

Combustion and Ventilation Air

unused heat removed by the ventilation air	128	kW
air temperature at the ventilation inlet min / max	20 - 35	°C
air temperature at the ventilation recommended	25	°C
amount of combustion air	7715	Nm ³ /hr
max. amount of ventilation air at the outlet flange	47141	m ³ /hr
max. air temperature at the outlet flange	50	°C
max. counter-pressure on flanges of ventilation air ¹⁾	120	Pa

1) total sum of pressure losses of connected ventilation pipeline without necessity of using additional fun

Exhaust Gas and Condensate Outlet

amount of exhaust gases	8365	Nm ³ /hr
exhaust gas temperature between engine-generator set and exhaust exchanger nominal / max	434/550	°C
exhaust gas temperature, nominal / max	150/180	°C
permissible pressure loss of the interconnecting and following exhaust piping	10	mbar
speed of exhaust gases at the outlet (DN 500)	18,3	m/s

Lubricant Charges

amount of lubrication oil in the engine	300	dm ³
volume of engine additional oil tank	685	dm ³
replenishment oil tank volume	650	dm ³

Noise Parameters

version	standard	option ¹⁾	
sound enclosure of CHP unit at 1m	86		dB(A)
ventilation inlet and outlet at 1m from the silencer	80	65	dB(A)
exhaust gas outlet at 1m from the silencer flange	80	60	dB(A)

1) noise parameters can be reduced by optimizing components to the required acoustic pressure level



Electrical Parameters

nominal voltage	230/400	V
nominal frequency	50	Hz
power factor ¹⁾	0,81	
nominal current at cos φ=0.8	3600	A
generator circuit breaker	NW40 H1 3P	
short-circuit resistance of switchboard R1	40	kA
short-circuit resistance of switchboards R2, R3, R4 and R5	10	kA
contribution of the actual source to the short-circuit current	< 40	kA
protection of power switchboard R1 closed/open	IP 31/00	
protection of control switchboard R2 closed/open	IP 31/00	
protection of frequency changers' switchboard R3 closed/open	IP 31/00	
protection of engine switchboard R4 closed/open	IP 31/00	
protection of cooling switchboard R5 closed/open	IP 66/00	
recommended superior protection	4000	A
recommended connection cable ²⁾ (< 50m, at t<35°C)	9×NYY (3×240+120)	

1) Power factor adjustable from 0,81C ÷ 1 ÷ 0,81L (range from 0,81C ÷ 1 must be verified according to the various types of generators).
 L = inductive load - overexcited
 C = capacitive load - underexcited
 Operation of the generator with a power factor of less than 0.95 causes a power limitation sets the following table:

power factor [-]	1	0,95	0,81
output [% Pnom]	100	100	98

2) The stated cables are for information only. A check calculation for temperature rise and voltage drop must be made according to the actual length, placement and type of the cable (maximum allowed voltage drop is 10 V)

Colour Version

engine and generator	RAL 5010 (blue)
base frame	RAL 9017 (black)
sound enclosure	RAL 5013 (blue)

Unit Dimensions and Weights

	Engine generator set	Exhaust gas module	
length	10100	6000	mm
width	2650	1500	mm
height	4250	3200	mm
service weight	29920	6150	kg

Ventilation silencer			
length	2180		mm
width	2080		mm
height	3000		mm
service weight	2880		kg

Exhaust silencer			
length	6800		mm
width	ø 1100		mm
height	horizontal		mm
service weight	1400		kg

Switchboards	height [mm]	width [mm]	depth [mm]
R1	2100	800/1000	800/1000
R2	2100	1600	400
R3 ⁽¹⁾	2100	600÷1200	500
R4 ⁽²⁾	1200	800	300
R5 ⁽³⁾	430÷1060	330÷855	200÷350

Overall service weight 1000 kg

1) Dimensions depend on direction of power outlets:
 Passing through switchboard = 2100x800x800 mm
 One direction = 2100x800x1000 mm

Width of switchboard R1 may be extended in special cases.

2) Switchboard's width depends on size of frequency changers.

3) Switchboard's height depends on MWM. Standard is 1200 mm.

4) Switchboard's dimension depends on number of dry coolers' fans.

Caution

Manufacturer reserves the right to alter this document and the linked source materials.

