

## Model: PHG50Pe



### **GENERATORS AND UPS**



- Intelligent Auto-Start
  Controller with Generator
- Monitoring and Protection Systems Suitable for Remote Starting or Connection with shentongroup AMF Panel
- Battery Trickle Charger
- Thermostatically controlled Engine Heater
- Long Range Bunded Base Fuel Tank
- Ability to be Customised to Specific Requirements
- Output Circuit Breaker

#### **GENERAL**

Shenton Group Generators range from 10 to 2500kVA, and are built to a world-class standard. These remarkably competitive standby generators provide the most cost-effective solution for 'standard package' requirements.

A first-class range of diesel-powered generators for prime and standby power application which feature reliable components from leading manufacturers, these are premium products upon which your company can build its reputation.

Model PHG50Pe		
Chandles Bassas	kVA	50
Standby Power	kW	40
Prime Power	kVA	45
	kW	36
Rated Speed	r.p.m	1500
Voltage	V	400/230
Rated Power Factor	Cos Phi	0,8
Data Sheet Number		PHG50Pe NS Rev 4

Prime: This rating is for the supply of continuous electrical power (at variable load) in lieu of commercially purchased power. There is no limitation on the annual hours of operation and 10% overload power can be supplied for one hour in twelve hours.

Standby: This rating is for the supply of continuous electrical power (at variable load) in the event of a utility power failure. No overload is permitted. Max rating, is available for one in twelve hours

Note: Standard reference conditions: 25deg C (77deg F) air inlet temperature, 152.4m (500feet) above sea level, 60% relative humidity. All engine performance data based on the above mentioned maximum continuous ratings. Fuel consumption data at full load for diesel fuel with specific gravity of 0.85 and conforming to BS2869: 1998, class A2.

In line with our policy of continuous development, we reserve the right to change specification without notice.



Model: PHG50Pe







ENGINE		
Rated Output	kWm	46.5
Manufacturer		Perkins
Model		1103A-33TG1
Engine Type		Diesel 4 Strokes-Cycle
Aspiration Type		Turbo charged
Cylinders Arrangement		3 in line
Bore & Stroke	mm	105 x 127
Displacement	L	3.3
Cooling System		Water
<b>Compression Ratio</b>		17.25:1
Fuel Consumption 100% PRP	l/h	10.7
Fuel Consumption 75% PRP	l/h	8.2
Fuel Consumption 50% PRP	l/h	5.7
Total Oil Capacity	L	8.31
<b>Total Coolant Capacity</b>	L	10.21
Governor	Туре	Mechanical
Air Filter	Туре	Dry Paper Cartridge
Battery Capacity	Ah	90
Battery Voltage	V	12

Perkins engines have a proven reputation within the generator industry, providing high levels of reliability and low cost of ownership. Perkins actively pursues product support excellence providing a consistent quality of support across the globe. shentongroup have used Perkins engines as our first choice product, for many years and found them to be solid, reliable and readily accepted products.



**Model: PHG50Pe** 







ALTERNATOR		
Manufacturer		Mecc Alte
Model		ECP 32-2S/4c
Poles		4
Frequency	Hz	50
Insulation Class		Н
Efficiency at 75% load class H 400v	%	88.7
Reactance Xd" Unsaturated	%	11.9
Reactance Xd' Unsaturated	%	15.9
Reactance Xo Unsaturated	%	3.04
Short Circuit Current Capacity	%	>300
Heat Dissipation 400v	W	5096
Radio Interference		EN50081-1, EN50082-1, VDE0875K
Waveform Distortion (THD) at Full Load	%	2.0%
Enclosure (according IEC-34-5)		IP 21
Weight of Complete Generator	Kg	165
Cooling Air Requirement	m3/min	15.7
Overload	%	1 in 6 hours
Overload per 20 sec	%	300
Exciter System		Auxilliary Winding
Voltage Regulator		DSR
Voltage regulation Performance +/-	%	1
Coupling		Flexible Disk

Linz Electric S.P.A., specialised in the production of alternators and rotating welders, was founded in 2002 under the guidance of engineer Giulio Pedrollo and quickly became a major player in the sector. Part of the Pedrollo Group, the company aims to create original and innovative solutions in energy transformation, thanks to the ten years' experience of its designers and to an advanced, and largely automated, production process.



Model: PHG50Pe



# **APPLICATION DATA**

Exhaust System		
Maximum Exhaust Temperature	°C	537
Exhaust Gas Flow	M3/min	7.7
Maximum Allowed Back Pressure	kPa	8

Air Flows		
Intake Air Flow	m3/h	186
Cooling Air Flow	m3/s	.883
Available Air Restriction		N/A

Fuel System		
Fuel Oil Spec		DIESEL
Fuel Tank Capacity	L	260
Autonomy @ 75% load	Hrs	32.5

Enclosure Specs		
Length	mm	2300
Width	mm	900
Height	mm	1357
Dry Weight	Kg	1120
Sound Pressure Level @ 7 mtrs	dB(A)	70

Electrical		
Output Circuit Breaker	Туре	МСВ
	Model	ABB S204B 80 Amps
Max Load Current at 400V .8 p.f.	Amps	72



Model: PHG50Pe







#### SG7410MKii GENERATOR CONTROLLER

The SG7410MKii is an Auto Start Control Module. Monitoring an extensive number of engine parameters, the modules will display warnings, shutdown and engine status information on the backlit LCD screen, illuminated LEDs, remote PC. The modules include USB, RS232 and RS485 ports as well as dedicated DSENet® terminals for system expansion. The module is compatible with electronic (CAN) and non-electronic (magnetic pick up/alternator sensing) engines and offers an extensive number of flexible inputs, outputs and engine protections so the system can be easily adapted to meet the most demanding industry requirements. The full list of features includes enhanced event and performance monitoring, remote communications and dual mutual standby.


CONTROL PANEL DISPLAY FEATURES		
Engine RPM	Generator Output Current	
Engine Oil Pressure	Earth current	
Coolant temperature	Output kW	
Battery Volts	Load level %	
Run Hours/ No of starts	Output kVA	
Fuel level	Power factor	
Generator output Voltage	Load kVAr	
Frequency	kWh/kVAh/kVArh	

SG7410MKii is a branded Deep Sea Electronics controller, customized to shentongroup's specific requirements. shentongroup has a long history of collaboration with Deep Sea Electronics, and endorse their products with confidence. Our experience has proved this is the market-leading controller having a perfect mix of complex capability and user simplicity.



Model: PHG50Pe





The above illustration is a representation only for preliminary planning. Specific detailed drawings are available on request. In line with our policy of continuous development, we reserve the right to change specifications without notice.