

Flexi 350

NG | 50Hz

OPEN MODULE | SOUND ENCLOSURE | CONTAINER

Basic technical data

Electrical output	354 kW	Voltage	400 V
Heat output nominal/max. ¹⁾	440/483 kW	Frequency	50 Hz
electrical efficiency	40,0 %	Service weight	
heat efficiency nominal/max. ¹⁾	49,8/54,6 %	- open module (OM)	8 t
total efficiency nominal/max. ¹⁾	89,8/94,6 %	- sound enclosure (SE)	9 t
fuel input	884 kW	- container (C)	17 t
secondary circuit temperature inlet/outlet	70/90 °C		

1) Heat output is a sum of secondary and aftercooler circuit heat outputs. Max. heat output (max. efficiency) of CHPU using NG or LPG is valid if the economiser is used and return water temperature is 35°C. For biogas fuels the usage of an economiser is not permitted.

Emission		lean mixture + oxidation catalyst	lean mixture + oxidation catalyst + SCR	
NOx emission at 5% O2 in exhaust gas standard/option		500/-	95/-	mg/Nm ³
CO emission at 5% O2 in exhaust gas standard/option		650/250	650/250	mg/Nm ³
HCHO emission at 5% O2 in exhaust gas standard/option		60/20	60/20	mg/Nm ³
Noise parameters		standard	silent ¹⁾	
OM	- CHPU at 1m	92		dB(A)
	- exhaust gas outlet at 1m from silencer flange ²⁾	65		dB(A)
SE	- CHPU at 1m	76	65	dB(A)
	- ventilation inlet/outlet at 1m	92	65	dB(A)
C	- exhaust gas outlet at 1m from silencer flange ²⁾	65	65	dB(A)
	- CHPU at 10m	59		dB(A)

1) Option.

2) Noise parameters can be further optimized according to the specific requests (option).

Notes

The Basic Technical Data are applicable for the standard conditions pursuant to the "Technical instructions" document. The minimum permanent electrical output must not drop below 50 % of the nominal output. Gas consumption is expressed under the invoicing conditions (15°C, 101.325 kPa) and gas LHV 34 MJ/m³. Gas consumption tolerance, or fuel input tolerance, at 100% load is +5%. Tolerances of other parameters are mentioned in "Technical Instructions-Validity of Technical Data" document.

Flexi 350

NG | 50Hz

OPEN MODULE | SOUND ENCLOSURE | CONTAINER

Extended technical data

Standard design	100%	75%	50%		Optional designs	ECO ²⁾	ECO-C ³⁾	
electrical output	354	266	177	kW	electrical output	354	354	kW
heat output ¹⁾	440	346	248	kW	max. heat output	460	483	kW
gas consumption	94	72	50	m ³ /h	fuel input	884	884	kW
fuel input	884	679	472	kW	electrical efficiency	40,0	40,0	%
electrical efficiency	40,0	39,1	37,5	%	heat efficiency	52,0	54,6	%
heat efficiency	49,8	51,0	52,5	%	total efficiency	92,0	94,6	%
total efficiency	89,8	90,1	90,0	%				

1) Heat output is a sum of secondary and aftercooler circuit heat outputs with exhaust gas cooled to 120°C.

2) Design with economiser (ECO) with return water temperature 70°C.

3) Design with economiser (ECO-C) with return water temperature 35°C.

Electrical parameters

voltage	400 V	operational current at cos φ=0,9	568 A
frequency	50 Hz	short circuit resistance of the switchboard	25 kA
nominal current	630 A	contribution of the actual source to the short-circuit current	< 6,5 kA
nominal power factor (GCB settings)	0,81	cos φ regulation range (underexcited/overexcited) ¹⁾	0,9±1÷0,9

1) Operation of generator with power factor lower than 0,98 decreases generator efficiency, what can cause reduction of the CHPU active power.

Engine / Generator

Engine	E3268 LE212	Generator	LSA 47.2 M7
producer	MAN	producer	LEROY SOMER
oil consumption normal/max.	0,19/0,38 g/kWh		
quantity of oil in the engine	95 dm ³		
volume of oil tank for refilling	220 dm ³		

Flexi 350

NG | 50Hz

OPEN MODULE | SOUND ENCLOSURE | CONTAINER

Heat system

Secondary circuit

heat carrier: water	
heat output	423 kW
inlet/outlet temperature	70/90 °C
min./max. inlet temperature	50/70 °C
nominal flow	5,1 kg/s
max. allowed pressure in circuit	1600 kPa
volume	56 dm ³
pressure drop at nominal flow	15 kPa

Primary circuit

heat carrier: antifreeze	
ethylene glycol concentration	40 %
heat output	423 kW
max. allowed pressure in circuit	350 kPa
volume	315 dm ³

Aftercooler circuit

heat carrier: antifreeze	
ethylene glycol concentration	40 %
heat output	16,0 kW
max. inlet temperature	42 °C
nominal flow	0,8 kg/s
pressure reserve at nominal flow (OM/SE/C)	30/30/0 kPa
min. inlet pressure	100 kPa
max. allowed pressure in circuit	250 kPa
volume (OM/SE/C)	10/10/10 dm ³

Exhaust gas

amount	1834 kg/h	temperature at the CHPU outlet nominal/max.	120/150 °C
temperature at the engine outlet	474 °C	max. allowed back-pressure	1 kPa

Fuel

natural gas		pressure (OM, SE)	3-10 kPa
low heat value	34 MJ/m ³	pressure (C)	5-10 kPa
min. methane number	80	max. temperature	35 °C

Combustion and ventilation air

Combustion air

ambient temperature min./max. (OM, SE)	10/35 °C
ambient temperature min./max. (C)	-20/35 °C
amount	1765 kg/h

Flexi 350

NG | 50Hz

OPEN MODULE | SOUND ENCLOSURE | CONTAINER

Ventilation	OM	SE	C	
unused heat removed by the ventilation	32	32	32	kW
max. amount of ventilation air at the outlet flange		8500		m ³ /h
max. air temperature at the outlet flange		50		°C
max. back-pressure at the ventilation air inlet flange		50		Pa
max. back-pressure at the ventilation air outlet flange		50		Pa

Related documents

dimensional drawing OM	R2291
dimensional drawing SE	R2530
dimensional drawing C	R2270